

YUMA INDUSTRIES

YUMAGE CLEANING APPLICATION GUIDE

LIQUID PRODUCTS	ALKALINITY	AMINES	CAUSTIC KOH of NaOH	CARBONATES	SILICATES	COMPLEX PHOSPHATES	CHELANTS	SOLVENTS	RUST PREVENTATIVE	ANIONICS	NON IONICS	AMPHOTERIC	SOAP	MINIMUM USE TEMPERATURE	pH @USING CONCENTRATION	IMMERSION	RECIRCULATION SPRAY	FERROUS	ALUMINUM SAFE	ZINC SAFE	MAGNESIUM SAFE	COPPER SAFE	RINSABILITY	FLASH POINT	REC'D USE CONCENTRATION	REMARKS
YUMAGE O-250								X						AMB.	N/A	X		X	X	X	X	X		208° F	UND.L.	LOW ODOR SAFETY SOLVENT DEGREASER
YUMAGE O-250A								X						AMB.	N/A	X		X	X	X	X	X		167° F	UND.L.	SAFETY SOLVENT DEGREASER
YUMAGE O-250H								X						AMB.	N/A	X		X	X	X	X	X		172° F	UND.L.	SAFETY SOLVENT DEGREASER / CITROUS ODOR
YUMAGE ST-210	H	X	X				X	X		X				AMB.	13.50			X					E	N/A	1:8	REMOVAL OF TRANSIT COATINGS
YUMAGE W-180	M	X							X				X	AMB.	10.10	X	X	X	X	X	X	X	E	N/A	2%-5%	LIGHT TO MEDIUM DUTY CLEANER / RP
YUMAGE W-29	L					X	X					X		AMB.	8.60			X						N/A	10%-100%	ROLLING MILL COIL STOCK CLEANER
YUMAGE W-60	M	X			X				X		X			120° F	11.50	X	X	X	X					N/A	1:10	ALUMINUM SPRAY, WASH CLEANER
YUMAGE W-71	H		X		X		X				X			120° F	12.50	X	X	X					E	N/A	2%-5%	ALUMINUM SPRAY, WASH CLEANER
YUMAGE W-75	M		X		X		X				X			120° F	12.50	X	X	X	X				E	N/A	2%-5%	ALUMINUM SPRAY, WASH CLEANER
YUMAGE W-80	L	X	X				X		X		X			AMB.	8.80	X	X	X	X	X		X	E	N/A	2%-5%	CLEANING MACHINED FERROUS PARTS
YUMAGE W-90	L	X	X				X		X		X			AMB.	9.70	X	X	X	X	X		X	E	N/A	2%-5%	MACHINED FERROUS PARTS-DEA FREE
YUMAGE WCB-1	N/A										X			130° F	7.00		X	X	X	X	X	X	E	N/A	0.50%	CLEANING BOOSTER
YUMAGE WCB-3	N/A							X			X			120° F	3.40		X	X	X	X	X	X	E	N/A	0.50%	CLEANING BOOSTER / SOLVENTIZED
YUMAGE WCW-1	L	X					X			X				AMB.	8.90		X	X	X	X	X	X	E	N/A	1:30	AUTOMATIC CAR WASH SOAP (BRUSH TYPE)
YUMAGE WDC--900	L	X					X	X		X	X			AMB.	8.40			X	X	X	X	X	E	113F	1:20	SOLVENTIZED GEN. PURPOSE CLEANER / CITROUS TYPE
YUMAGE WGP-600	L	X					X	X		X	X			AMB.	8.70	X		X	X	X	X	X	E	N/A	1:20	GENERAL PURPOSE CLEANER
YUMAGE WFC-300	H		X			X	X	X		X	X			AMB.	12.40	X		X					E	N/A	5%-10%	MANUAL FLOOR CLEANER (HEAVY DUTY)
YUMAGE WHT-1100	H		X				X				X	X		AMB.	13.20	X		X					E	N/A	1:5	HD IMMERSION HOT TANK CLEANER FOR FERROUS METALS
YUMAGE WHT-1300	L	X								X	X			120° F	9.30	X		X	X	X	X	X	E	N/A	1:7	MED. DUTY IMMERSION HOT TANK CLEANER FOR SOFT METALS
YUMAGE WMC-150	L							X			X			AMB.	9.50	X		X	X	X	X	X	E	N/A	1:20	COOLANT SYSTEMS CLEANER / CITROUS TYPE
YUMAGE WSW-100	H		X			X	X			X				120° F	13.10	X	X	X					E	N/A	2%-5%	HEAVY DUTY SPRAY WASH CLEANER
YUMAGE WSW-100S	H		X			X	X		X	X				120° F	13.20	X	X	X					E	N/A	2%-5%	HEAVY DUTY SPRAY WASH CLEANER-FERROUS
YUMAGE WSW-1029T	M	X	X	X	X			X				X		AMB.	11.70	X	X	X	X	X	X	X	E	N/A	0.5%-5.0%	SOFT METAL SAFE SPRAY WASH CLEANER / RP
YUMAGE WSW-240AL	H	X	X		X		X		X	X	X			110° F	12.90		X	X	X	X	X	X	E	N/A	2%-5%	SILICATED SOFT METAL SAFE SPRAY WASH
YUMAGE WSW-242AL	M					X				X	X			120° F	9.20		X	X	X	X	X		E	N/A	2%-5%	NON-SILICATED SOFT METAL SAFE SPRAY WASH
YUMAGE WSW-243AL	M	X				X	X		X	X	X			120° F	9.00		X	X	X	X	X	X	E	N/A	2%-5%	SAME AS 242AL+IRON+COPPER INHIBITOR
YUMAGE WSW-250	H		X		X		X	X		X				120° F	12.90		X	X					E	N/A	1:20	ALKALINE / SOLVENTIZED SPRAY WASH CLEANER FOR FERROUS METALS

YUMA INDUSTRIES

YUMAGE CLEANING APPLICATION GUIDE

LIQUID PRODUCTS	ALKALINITY	AMINES	CAUSTIC KOH or NaOH	CARBONATES	SILICATES	COMPLEX PHOSPHATES	CHELANTS	SOLVENTS	RUST PREVENTATIVE	ANIONICS	NON IONICS	AMPHOTERIC	SOAP	MINIMUM USE TEMPERATURE	pH @USING CONCENTRATION	IMMERSION	RECIRCULATION SPRAY	FERROUS	ALUMINUM SAFE	ZINC SAFE	MAGNESIUM SAFE	COPPER SAFE	RINSABILITY	FLASH POINT	REC'D USE CONCENTRATION	REMARKS
YUMAGE WSW-260AL	L		X			X				X	X			110 ⁰ F	7.0		X	X	X	X		X	E	N/A	2%-5%	NEUTRAL SPRAY WASH NON RINSING
YUMAGE WSW-280	L	X							X					AMB.	9.80	X	X	X	X				E	N/A	2%-5%	MILD CLEANER + RP FOR FERROUS METALS
YUMAGE WTC-1750	M				X		X	X			X			AMB.	11.60	X		X	X	X			E	N/A	1%-10%	AUTOMATIC FLOOR SCRUBBER SOAP / GEN. PURPOSE CLEANER
YUMAGE WTC-1800	L			X			X	X			X			AMB.	9.50	X		X	X	X	X	X	E	N/A	1%-10%	AUTOMATIC FLOOR SCRUBBER SOAP / GEN. PURPOSE CLEANER
YUMAGE WVC-500	H		X			X	X		X	X				AMB.	12.20	X		X					E	N/A	1/2%-2%	VIBRATORY FINISHING FERROUS ONLY
YUMAGE WVC-750	L	X							X					AMB.	9.0	X	X	X	X	X	X	X	E	N/A	0.5%-2%	VIBRATORY FINISHING / SPRAY WASH RP

X:\Customer_Projects\PRODUCTION\com\yumaindustries\customer_source\yumage_chart.xls]Sheet1